

# PAX 42PRO

# PAX 42BT (option)

<b>Box</b>	<b>2 way, bass-reflex</b>	<b>2 way, bass-reflex</b>
<b>Pm / Pn</b>	<b>400 / 250 W</b>	<b>400 / 250 W</b>
<b>Pamp class A-B</b>	<b>-</b>	<b>250 W<sub>RMS</sub></b>
<b>Z</b>	<b>8 Ohm</b>	<b>4 Ohm</b>
<b>f</b>	<b>35-20.000 Hz</b>	<b>35-20.000 Hz</b>
<b>Spl (1W/1m)</b>	<b>96 dB</b>	<b>96 dB</b>
<b>S/N ratio</b>	<b>-</b>	<b>≥85 dB</b>
<b>∅ Woofer / ∅ Coil</b>	<b>15" (380mm)</b>	<b>15" (380mm)</b>
<b>Voice coil / Magnet</b>	<b>75 mm / 60 Oz</b>	<b>75 mm / 60 Oz</b>
<b>Tweeter diaphragm</b>	<b>1,75" titanium (44mm)</b>	<b>1,75" titanium (44mm)</b>
<b>Tweeter magnet</b>	<b>23 Oz</b>	<b>23 Oz</b>
<b>FM RADIO</b>	<b>-</b>	<b>87,6-108,0 MHz</b>
<b>BT VERSION</b>	<b>-</b>	<b>v5.0 / TWS</b>
<b>BT ERP</b>	<b>-</b>	<b>10m max.&lt;1mW</b>
<b>USB / SD</b>	<b>-</b>	<b>FAT32 / 32GBmax.</b>
<b>FILE FORMATS</b>	<b>-</b>	<b>MP3-WMA-FLAC-WAV-APE</b>
<b>MIC INPUT</b>	<b>-</b>	<b>∅6,3 mm + XLR</b>
<b>LINE INPUT</b>	<b>-</b>	<b>2 x RCA + XLR</b>
<b>LINE OUTPUT</b>	<b>-</b>	<b>∅6,3 mm + XLR</b>
<b>SPEAKER IN</b>	<b>Speakon (1 x 8 Ohm)</b>	<b>-</b>
<b>SPEAKER OUT</b>	<b>-</b>	<b>Speakon (1 x 8 Ohm)</b>
<b>Stand / ∅</b>	<b>35 mm</b>	<b>35 mm</b>
<b>T<sub>a</sub></b>	<b>0°C...+35°C</b>	<b>0°C...+35°C</b>
<b>V / Hz / W</b>	<b>-</b>	<b>230V~ / 50Hz / 250W</b>
<b>Dimensions</b>	<b>~45 x 71 x 37 cm</b>	<b>~45 x 71 x 37 cm</b>
<b>kg</b>	<b>16,5 kg</b>	<b>18,5 kg</b>