

SPEAKER SPECIFICATION

System	2x tweeter + woofer + 2x passive sub-bass radiator
Functions	BT TWS/USB/microSD/AUX/WIRELESS MIC
Input, wired	AUX 3.5mm, stereo
Input, wireless	BT TWS STEREO
Bluetooth freq. range	2.402-2.480GHz
Bluetooth ERP	≤2.5mW / ~10 m max.
Bluetooth TWS	v5.3+BR+EDR+BLE
BT profiles	A2DP/AVRCP/HFP/HSP/OPP/ HID/SPP/PBAP/GATT/SM
USB file system	FAT32, max.64GB, stereo
Audio file	MP3
Pmax/Pnom	100 / 65 Watt
Tweeters	2 x 30 / 20 W (66mm)
Woofer	1 x 40 / 25 W (135mm)
Sub-bass	2x passive radiator (180x85mm)
f	40 - 20.000 Hz
THD	≤5 %
S/N	≥80 dB
USB-C charge	5 V [~] / 2.5 A max.
Battery, 4x18650	7.4 V 10.400mAh ~77 Wh
Charging time	~5 h
Operation time	~9 h
Stand socket	Ø35 x 50 mm
Waterproof	IPX5 level
Ta	0 °C...+40 °C
Dimensions / Weight	255x276x248 mm / 3.5 kg

MICROPHONE SPECIFICATION

Operation range	~30 m (in open area)
Mic element	dynamic capsule
Characteristic	cardioid
Nominal freq. range	~606-690 MHz UHF
Fixed frequency	data on handy's label
ERP output	<10 mW
Batteries	2x AA (1.5 V) / 1pc handy
Ta	5 °C...+35 °C
Dimensions	Ø50/33 x 250 mm
Weight	2x 190 g